


REV.	LOCAS	DESCRIPTION	DATE	DRAWN
01	NEW	INITIAL RELEASE	08-24-02	C-1-KANG
02	△	變更塑膠材質	07.11.06	周禮軍
03	△	變更封裝	2008.08.04	彭思城
04	△	變更圖號	2011.01.09	黃明霞

Specifications
 Current Rating: 1Amp
 Insulation Resistance: 1000MΩMin.
 Dielectric Withstanding: 300VAC
 Contact Resistance: 20mΩMax.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 LCP
 All materials must meet Greenconn requirement for environment protection.

Recommended P.C.Board
 Hole Layout



Ordering Information

G PEA101 - XX XX A001 C 1 A X



No. of Pins per Row Contact Plating
 01=Tin
 02=Gold Flash
 Duplex plating
 05=Gold Flash /Tin

Options
 D=tape reel
 F=cap+tape reel
 ...

格菱股份有限公司
Greenconn Corporation

REV. 04	UNIT. mm	SCALE. 1:1	PAGE. 1/1				GENERAL TOLERANCE	DESIGN: 黃明霞	DATE: 2011.01.09	DWG. NO. △ GPEA101-CA1CA	TITLE: 1.27PIN HEADER SINGLE ROW DIP TYPE BASE 2.54 H
				X:±5.0°	X:±3.0°	.XX±2.0°	X:±0.30	CHECKED: 李新華	DATE: 2011.01.09	PART NO. △ GPEA101-XXXXA001C1AX	
				.XX±2.0°	.XX±0.15	.XXX±1.0°	X:±0.25	AUDITED: Lear	DATE: 2011.01.09		